



DOOR HEIGHT (m)	HEADROOM (DIM X)	INSIDE PROJECTION MOTOR (DIM Y)	INSIDE PROJECTION BARREL (DIM Z)
0 - 1.25	420mm	360mm	360mm
1.25 - 2.0	430mm	370mm	370mm
2.0 - 3.0	450mm	385mm	385mm
3.0 - 4.0	450mm	400mm	400mm
4.0 - 4.5	450mm	430mm	430mm

PLEASE NOTE THE UP/DOWN BUTTONS AND SINGLE PHASE PLUG ARE INTENDED FOR SITE COMMISSIONING OF DOOR ONLY. IF RETAINED AS SURFACE MOUNTED, ANY CABLING UNDER 2m FROM FFL MUST BE PROTECTED. PUSH BUTTONS CAN BE REMOVED FROM ENCLOSURE AND FLUSH MOUNTED INTO WALL OR REPLACED WITH A KEY SWITCH (KEY SWITCH NOT INCLUDED).

We reserve the right to alter specification without notice and without incurring obligation

STEEL ROLLER SHUTTER – WINDLOCK GUIDES  
INTERNAL BARREL MOTORISING – GENERAL ARRANGEMENT



C	13.12.13	TS	MATERIAL – FINISH	CODE No.	SCALE	:	DRG No.	ISS.
B	28.05.13	TS			DRAWN	TS	24.04.13	
ISS.	DATE	BY			APPVD.		SRS_WL_IBM	C